



INCREASED EFFECTIVENESS: MORE FOAM THAN WATER ON THE SURFACE

Agoston RESTAS

ZVÝŠENÁ ÚČINNOSŤ: VIAC PENY AKO VODY NA POVRCHU



ENVIRONMENTAL POLICY TOOLS '2016

Abstract

Introduction: The effectiveness of the foams used in fighting against forest fire depends on common effect of some coefficients. Cooling and isolation effects as well as side extinguishing effects, like evaporation, blanket and separation effects are also included. Under the same conditions, the more extinguisher remains on the surface, the more extinguishing effect it has. Methods: A product for the test was randomly chosen out of the ones on the market. Spruce was chosen for the test due to its high flammability. The goal was to determine the amount of extinguisher at the end of the branches in the foliage. Results: The amount of foam remaining on the foliage is remarkably higher than that of water. Its rate is 3.36-3.76 compared to water. The research also revealed that this rate does not significantly depend on expansion rate.

KEY WORDS: *suppression capability, foam, weight effectiveness experiment, R-10A method*

1. Introduction

The effectiveness of the foams used in fighting against forest fire depends on common effect of some coefficients. Cooling and isolation effects as well as side extinguishing effects, like evaporation, blanket and separation effects are also included (Kuncz, 1972). The efficiency of isolation effect certainly depends on the amount of extinguishing agent measured in unit area of surface, which in the case of not horizontal surfaces is in correlation with the adhesion of the extinguisher that is the rate of remaining on the surface. Under the same conditions, the more extinguisher remains on the surface, the more extinguishing effect it has.

Since the quantity of the extinguisher has a great impact on the firefighting techniques applied as well as the effectiveness of the techniques applied (Bleszity, 1990), it is recommended to review the various factors not only because of their importance but also because of the safety of the intervention crew (Pantya, 2011). Several studies are dealing with the effectiveness of extinguishers and separate measurement methods were created (Batista, 2011; Morris, 2011). However, researches aimed at the extinguisher remaining on the foliage may be scarce, according to the author. The paper wishes to present a unique approach to this topic, comparing water and foam as extinguishers with different structures and their ability to remain on the surface. This procedure following the below assumptions got a fantasy name and was called R-10A method.

2. Methods

The method was developed in order to measure the rate of foam remained on the vegetation surface (spruce) to determine the extinguishing potential of foam blanket. This problem can have not just one aspect. In case of using very "light" foam – meaning that the expansion rate of foam is large, with other words the density is low – it will remain on the top of the crown, therefore it is unable to protect the bulk from the radiation heat or it can be blown over by the wind. In other case, when using very "heavy" foam – meaning that the expansion rate is low or the density is high – it takes the features as Newtonian fluid and will drip to ground resulting that the larger



part of foam will not remain in the area of the burning cell. Both case causes useless waste. Even if the ideal expenditure rate of foam can be different depending on the situation or the type of vegetation but author's experience say it must be higher than 6 but below 13. As a series in this research author used foams expenditure rate of 6 – 9 – 12.

The other aspect is that, what is the difference between the weights of the extinguisher materials remaining on the surface (crown).




Figure 1 – Structure of foam remaining on the crown depending on the rate of expenditure

During the research the goal has been formulated to develop a simple, easily reproducible method used for both illustration and teaching which proves the differences in the extinguishers' adhesion and presents its consequences. The author opted for analysing the mass/volume of extinguishers left on the surface. A product was randomly chosen out of the ones on the Hungarian market. It is named Light Water, what is used in Hungary as common foam concentrate, even in case of serious forest fire, however this type of foam not typical at the international practice (or at forest fire). Using this foam is acceptable, because the aim of the test is not to determine the efficiency of the extinguisher, but to demonstrate its application.

Spruce was chosen for the test due to its high flammability. The goal was to determine the amount of extinguisher at the end of the branches in the foliage. Groups of the same size were created in the selected foliage. To start with, the weight of the untreated foliage was measured, followed by the groups of foliage dipped in water and foaming agents. In the case of the latter groups, the weight of the foliage itself was subtracted from the total weight, giving us the maximum amount of the extinguisher remaining on the foliage. During the experiment 6 – 9 – 12 expansion rated foams were applied.

Below is declared the main important things for preparing the test, and some basic process for being ready to measure the mass/volume foam left on the surface. Means required for the process:

- Choosing samples: The highly flammable spruce was chosen as a sample. Twigs of 100-150 mm were cut down (4x10pcs= 40pcs). Thus, that part of the spruce was examined which has the greatest role both in fire spread and keeping the extinguisher.
- Preparing the samples: the twigs are dried in sun for 4 hours in 30°C. Thus, the surface becomes totally dry similarly to the typical conditions of intense fire periods.
- Preparing the matrix holding the samples: a matrix was created according to the set of measurements. It included the boxes (altogether 4x10 pcs) to keep water and the foams of 6 – 9 – 12 expansion (Hk = 6 – 9 – 12).
- Preparing the extinguishers to be examined: normal tap water and foam-forming substance was used in the experiment. The foam-forming substance was Light Water, which is generally used in Hungary.
- The preparation of the extinguishers: Water was 20°C, normal temperature, 15 °dH (water hardness in German degrees). Preparing a foam solution in measuring bottles: the foam-forming substance is



Light Water, out of which foams of different expanditure were created, using a mixture of 3%. These were in three different bottles: Hk = 6; Hk = 9; Hk = 12.



Figure 2 – Preparing the spruce twigs for measurement

3. Measured data of different treated samples

The measurements clearly show that water and foam remain on the surface of the foliage in completely different shapes (Figure 3). Water is not evenly distributed, but it sticks to the surface in drops, separately, while the foam surrounds the twig in a homogenous mass. In spite of the conspicuous difference, we do not know if the difference in structure causes any significant difference in the extinguishers' ability to remain on the surface. If so, then the extinguisher which has more quantity on surface possesses more heat capacity proportionately.



Figure 3 – Different treated samples – foam and water

The findings of the measurements carried out and the values obtained from the data can be found in Table 1.



Table 1—Measured data

R-10A	Measured weight (gram)			
Weight of untreated samples (n=10) (avarage:34,17)	33,48	34,26	35,33	33,60
1. Sample group				
Weight of samples treated by water (net)	50,52	-	-	-
Weight of water	17,04	-	-	-
Rate of extinguisher (water) to max. water on surface	1	-	-	-
2. Sample group				
Weight of samples treated by foam, Hk=6 (net)	-	98,33	-	-
Weight of foam, Hk=6	-	64,07	-	-
Rate of ext. (foam, Hk=6) to max. water on surface	-	3,76	-	-
3. Sample group				
Weight of samples treated by foam, Hk=9 (net)	-	-	94,84	-
Weight of foam, Hk=9	-	-	59,51	-
Rate of ext. (foam, Hk=9) to max. water on surface	-	-	3,49	-
4. Sample group				
Weight of samples treated by foam, Hk=12 (net)	-	-	-	90,81
Weight of foam, Hk=12	-	-	-	57,21
Rate of ext. (foam, Hk=12) to max. water on surface	-	-	-	3,36

4. Calculations

The following calculations were made to assess the findings. To start with, the author specified the average weight of the samples from each sample group, and then calculated the weight of the individual sample by averaging.

Secondly, by dipping the samples into water, the author specified the maximum value of water saturation. Thus the water retention capacity of the samples can be determined, by considering the differences in weight.

Thirdly, foams of different expanditure and their ability to remain on the surface were examined. The samples were dipped into foam (it results also the maximum weight on surface), weighed and then the relevant data were calculated by averaging.

The ability of the extinguisher to remain on the surface was determined by subtracting the weight of the untreated samples from the values measured. Then we get the values of the foam by comparing these data to the data of the samples treated with water. The calculations produce the following results:

1. Average weight of the individual samples of the 4 sample groups

2.

$$\bar{m}_{P_Nature} = \frac{\sum_{i=1}^n m_{P_Nature_n}}{n} = \frac{33,48g}{10} = 3,348g$$

$$\bar{m}_{P_Nature} = \frac{\sum_{i=1}^n m_{P_Nature_n}}{n} = \frac{34,26g}{10} = 3,426g$$

$$\bar{m}_{P_Nature} = \frac{\sum_{i=1}^n m_{P_Nature_n}}{n} = \frac{35,33g}{10} = 3,533g$$



$$\bar{m}_{P_Nature} = \frac{\sum_{i=1}^n m_{P_Nature_n}}{n} = \frac{33,60g}{10} = 3,360g$$

3. Average of the average samples of the sample groups

$$\bar{m}_{P_Nature} = \frac{\sum_{i=1}^4 m_{P_Nature_n}}{n} = \frac{3,348g + 3,426g + 3,533g + 3,360g}{4} = 3,417g$$

4. The average weight of the spruce sample dipped into water

$$\bar{m}_{P_H_2O} = \frac{\sum_{i=1}^n m_{P_H_2O_n}}{n} = \frac{50,52g}{10} = 5,052g$$

5. The average weight of the spruce sample treated with foam of expenditure H_K

$$\bar{m}_{P_Foam_H_K=6} = \frac{\sum_{i=1}^n m_{P_FoamH_K_n}}{n} = \frac{98,33g}{10} = 9,833g$$

$$\bar{m}_{P_Foam_H_K=9} = \frac{\sum_{i=1}^n m_{P_FoamH_K_n}}{n} = \frac{94,84g}{10} = 9,484g$$

$$\bar{m}_{P_Foam_H_K=12} = \frac{\sum_{i=1}^n m_{P_FoamH_K_n}}{n} = \frac{90,81g}{10} = 9,081g$$

6. The average weight of the water on the spruce sample

$$\bar{m}_{H_2O} = \bar{m}_{P_H_2O} - \bar{m}_{P_Nature} = 5,052g - 3,348g = 1,704g$$

7. The average weight of the foam of expenditure H_K on the spruce sample

$$\bar{m}_{Foam_H_K=6} = \bar{m}_{P_Foam_H_K} - \bar{m}_{P_Nature} = 9,833g - 3,426g = 6,407g$$

$$\bar{m}_{Foam_H_K=9} = \bar{m}_{P_Foam_H_K} - \bar{m}_{P_Nature} = 9,484g - 3,533g = 5,951g$$

$$\bar{m}_{Foam_H_K=12} = \bar{m}_{P_Foam_H_K} - \bar{m}_{P_Nature} = 9,081g - 3,360g = 5,721g$$

8. The rate of foam of expenditure H_K and water on the spruce samples

$$R_{\gamma} = \frac{\bar{m}_{Foam_H_K=6}}{\bar{m}_{H_2O}} = \frac{6,407g}{1,704g} = 3,76$$

$$R_{\gamma} = \frac{\bar{m}_{Foam_H_K=9}}{\bar{m}_{H_2O}} = \frac{5,951g}{1,704g} = 3,49$$

$$R_{\gamma} = \frac{\bar{m}_{Foam_H_K=12}}{\bar{m}_{H_2O}} = \frac{5,721g}{1,704g} = 3,36$$



5. Results

According to the findings of research, the amount of foam remaining on the foliage is remarkably higher than that of water. Its rate is 3.36-3.76 compared to water. The research also revealed that this rate does not significantly depend on expansion rate. The surface of the foliage in a full-grown forest is able to hold 4-5 kgm⁻¹ water, which is enough to control a fire of about 3400 kWm⁻¹ fire intensity.

We can come to the conclusion that if fire intensity is so high that the cooling capability of water is not enough to extinguish the fire, applying foam can extend the range of extinguishing possibilities to dimension where extinguishing with water is not possible for objective reasons. Its reason is that by applying foam, the mass remaining on the surface, thus the cooling capability of the extinguisher, can be tripled. As a result, the fire intensity which can be extinguished expands as well.

We have to add that in addition to the foam's weight effectiveness increase, insulation effects can be noticed, too, resulting in additional extinguishing effects. Weight effectiveness and insulation effects do not add up but multiply, which is yet another proof of the advantages of foams.

The above results show that the factor of weight effectiveness of the foams is significant, which offers the opportunity of increasing the amount of extinguisher on one unit of surface. The unsatisfactory extinguisher effect of water can be improved and extinguisher solutions have become available which have been impossible so far.




Figure 4 – Rate of weight remained on surface depending on the expenditure rate of foams

Appendix A – Notation

1. $\overline{m_{P_Nature}}$ = the weight of the individual twig (sample), untreated;
2. $\overline{m_{P_Nature}}$ = the average weight of the untreated samples;
3. $\overline{m_{P_H_2O}}$ = the weight of the individual samples treated with water;
4. $\overline{m_{P_H_2O}}$ = the average weight of the samples treated with water;
5. $\overline{m_{P_Foam_K_k}}$ = the weight of the individual samples treated with foam of H_k expenditure;



6. $\overline{m_{P_Foam_K_k}}$ = the average weight of the samples treated with foam of H_K expanditure;
7. $\overline{m_{H_2O}}$ = the average weight of the water remaining on the samples;
8. $\overline{m_{Foam_H_k}}$ = the average weight of the foam of H_K expanditure remaining on the samples;
9. R_γ = the weight of the foam of H_K expanditure and water remaining on the samples;
10. $m_{\max H_2O_m^2}$ = the weight of the water remaining on one unit of surface (constant) = 5kg;
11. $m_{\max FoamH_k_m^2}$ = the weight of the foam of H_K expanditure remaining on one unit of surface.

Appendix B – Mathematical formulas used for calculations

1. The average weight of the untreated spruce sample

$$\overline{m_{P_Nature}} = \frac{\sum_{i=1}^n m_{P_Nature_n}}{n}$$

2. The average weight of the spruce sample dipped into water

$$\overline{m_{P_H_2O}} = \frac{\sum_{i=1}^n m_{P_H_2O_n}}{n}$$

3. The average weight of the spruce sample dipped into foam of H_K expanditure

$$\overline{m_{P_Foam_H_k}} = \frac{\sum_{i=1}^n m_{P_FoamH_k_n}}{n}$$

4. The average weight of the water remaining on the spruce sample

$$\overline{m_{H_2O}} = \overline{m_{P_H_2O}} - \overline{m_{P_Nature}}$$

5. The average weight of the foam of H_K expanditure remaining on the spruce sample

$$\overline{m_{Foam_H_k}} = \overline{m_{P_Foam_H_k}} - \overline{m_{P_Nature}}$$

6. The rate of the average foam of H_K expanditure and water remaining on the samples

$$R_\gamma = \frac{\overline{m_{Foam_H_k}}}{\overline{m_{H_2O}}}$$

7. The amount of water effectively remaining on one unit of surface

$$m_{\max H_2O_m^2} = \text{const} = 5kg$$

8. The amount of foam of H_K expanditure remaining on one unit of surface

$$m_{\max FoamH_k_m^2} = m_{\max H_2O_m^2} R_\gamma$$

References

- Batista, A.C.: Combustion characteristics tests of Magnolia grandiflora and Michelia champaca for potential use in fuelbreaks in south region of Brazil, Wildfire 2011 Conference, Sun City, South Africa, 2011.05.9-13.
- Bleszity, J., Zelenák, M.: Tűzvédelmi ismeretek (Firefighting basic knowledge), Budapest: Szövetkezeti Szervezési Iroda, 272 p. 1990



- Kuncz, I.: A tuz es oltoanyagai (Physics of fire and extinguishers), BM Kiado, Budapest, Hungary, p 240. 1972
Morris C.J.: A simulation study of fuel treatment effects in dry forests of the western United States: testing the principles of a fire-safe forest, Wildfire 2011 Conference, Sun City, South Africa, 2011.05.9-13.
Pantya, P.: A tűzoltói beavatkozás biztonságának növelése zárttéri tűzeknél (Safety of firefighters during interventions in different areas), HADMERNÖK 6: (1) pp. 165-171.

CONTACT ADDRESS

Author: Agoston Restas, PhD
Workplace: National University of Public Service, Budapest, Hungary
E-mail: Restas.Agoston@uni-nke.hu

RECENZIA TEXTOV V ZBORNÍKU

Recenzované dvomi recenzentmi, členmi vedeckej rady konferencie. Za textovú a jazykovú úpravu príspevku zodpovedajú autori.

REVIEW TEXT IN THE CONFERENCE PROCEEDINGS

Contributions published in proceedings were reviewed by two members of scientific committee of the conference. For text editing and linguistic contribution corresponding authors.